



TALAMONI s.n.c.
Sede legale e operativa:
Via Menconi, 3 - Cap.28877 Ornavasso (VB)
Tel. +39 0323 836198
E-Mail:contact@talamoni.com Sito internet: www.talamoni.com



Rel. # 2 on 01/02/2019

Technical note

Olío da taglio per vetro basso emissivo e magnetronico - alta evaporazione

MAIN FEATURES

Cutting oil for low-emissivity glass and magnetron - high evaporation.

Item Code: T-OIL 3132

Synthetic fluid for the evaporable glass cutting.

Oil for cutting glass with low emissivity, metallic and magnetron, high and complete evaporation. Do not leave any traces on the glass.

ADVANTAGES:

- Because of the low viscosity and easy volatility of the solvent, after a short time by the application remains the only active material;
- The active material has remarkable non-stick properties for which is rapid shearing of the workpiece even in the presence of profiles difficult;
- The percentage of active substance has been studied to obtain the right amount for the mechanical operation but also to obtain a piece that does not require a subsequent operation of degreasing;
- Any residue can come into contact with food because they respond to:
FDA 21 CFR 178.3910 on Surface lubricants used in the manufacture of metallic articles;

CHEMICAL-PHYSICAL FEATURES

Appearance: colorless liquid (+30)
Odour: characteristic
pH: Not applicable
Melting point/freezing point: < -30°C
Flash point: 66°C
Relative density: 0,765 Kg/l (20°C)
Water solubility: Insoluble
Viscosity: 1,47 mm²/s (40°C)

APPLICATIONS

Cutting and troncheggio of the glass.

The T-OIL 3132 has been specifically designed for:

- The base is easily evaporable solvent.
- The solvent is a low odor impact.
- The active substance is not oxidizable and thus not give rise to unpleasant odors even for a prolonged period of storage.
- The active material has excellent lubricating ability in cutting phase.
- The active material has an excellent property for cutting the glass.
- All components meet the FDA specifications for products that come into contact with food.

TIPS FOR USE

Manufactured by use pure.

PRECAUTIONS FOR USE

This product does not present any special risks if used according to our recommendations and applied correctly. A safety data sheet in compliance with the EU legislation is available from your sales advisor.
Store possibly indoors. If it is stored outdoors, keep the kegs in a horizontal position and cover them with a lid to avoid water infiltration. Do not store at temperatures above 60 °C or directly in the sun as it is good to keep them in places not subject to frost.
Protect the environment, avoid dispersion of used oil and containers.



TALAMONI s.n.c.
Sede legale e operativa:
Via Menconi, 3 - Cap.28877 Ornavasso (VB)
Tel. +39 0323 836198
E-Mail:contact@talamoni.com Sito internet: www.talamoni.com



Rel. # 2 on 01/02/2019

Technical note

Olío da taglio per vetro basso emissivo e magnetronico - alta evaporazione

PACKAGING

- DRUMS-208 LITRES.
- BUCKET 25 LITRE.
- 5 LITER BOTTLES.
- 1 LITER BOTTLES.

CLASSIFICATION AND LABELLING

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:
GHS08

Hazard Class and Category Code(s):
Asp. Tox. 1

Hazard statement Code(s):
H304 - May be fatal if swallowed and enters airways.

The product can be fatal if swallowed and enters airways

UN Number: 0000

Instructions: The instructions and the information brought on this document are fruit of experiences of laboratory and practical employment and therefore accurate and pertinent. Being the Royal conditions of use from the consumers aldilà of every possibility of ours of control, they are furnished on our behalf without some responsibility or guarantee, implicit or explicit. For further information we beg You to contact our Technical Service.